



TG-PCM095

Phase Change Materials

REACH Compliant RoHS Compliant

Features

- Good flow rate over phase change temperature
- Fully filled the gaps of contact surface
- Low thermal impedance

Applications


Electronic Components - 5G, Aerospace, AI, AIoT, AR/VR/MR/XR, Automotive, Consumer Devices, Datacom, Electric Vehicle, Electronic Products, Energy Storage, Industrial, Lighting Equipment, Medical, Military, Netcom, Panel, Power Electronics, Robot, Servers, Smart Home, Telecom, etc.

Storage

Shelf Life: 12 months at or below 25°C

Properties

Thermal Conductivity : 9.5 W/m·K



Properties	Unit	TG-PCM095	Test Method
Thermal Conductivity	W/m·K	9.5	ASTM D5470
Thickness	mm	0.20/0.25	ASTM D374
	inch	0.0079/0.0098	ASTM D374
Color	-	Gray	-
Phase Transition Temperature	° C	45	-
Density	g/cm³	2.55	ASTM D792
Operating Temperature	° C	-50~+140	-
Thermal Impedance @10psi	°C *in²/W	0.0173	ASTM D5470
Thermal Impedance @30psi	°C *in²/W	0.0063	ASTM D5470
Thermal Impedance @50psi	°C *in²/W	0.0057	ASTM D5470

※Die-cut for different shapes

T-Global USA LLC

2880 Zanker Road, Suite 103, San Jose, CA 95134, USA

T +1(669)345-0002

E usa@tglobal-usa.com

W www.tglobal-usa.com

T-PC003F-01



NOTICE: The information contained herein is to the best of our knowledge true and accurate. Values stated in this technical data sheet represent typical values as not all tests are run on each lot of material produced. All specifications are subject to change without notice. The protective film and release paper do not affect the function of the product. If there is no special requirement, the default depends on T-Global. Since the varied conditions of potential use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part and users should make their own test to determine the suitability of our products in any specific situation. This product is sold without warranty either expressed or implied, of fitness for a particular purpose or otherwise, except that this product shall be of standard quality, and except to the extent otherwise stated in T-Global Technology's invoice, quotation, or order acknowledgment. We disclaim any and all liabilities incurred in connection with the use of information contained herein, or otherwise. All risks of such are assumed by the user. Furthermore, nothing contained herein shall be construed as a recommendation to use any process or to manufacture or to use any product in conflict with existing or future patents covering any product or material or its use.